

## LISTING OF THE CLAIMS

The following listing, if entered, replaces all prior versions of the claims in the present application.

1. **(Currently Amended)** A method ~~for communicating~~ comprising:
  - obtaining an event communicated to a communication ~~center server~~ via an incoming communication channel of a plurality of communication channels, wherein the communication server is communicatively coupled to the plurality of communication channels via a plurality of channel drivers,
  - each communication channel of the communication channels has a media type,
  - at least two communication channels of the communication channels have different media types, and
  - the event corresponds to a work item available via the incoming communication channel;
  - providing a notification of the work item via a user interface, wherein the user interface comprises a web browser;
  - receiving an activation of a work item object of the user interface, wherein
    - the work item object is associated with the work item,
    - the activation of the work item object is associated with selecting one communication channel of the plurality of communication channels, and
    - the work item object is activated by an agent;
  - identifying one or more parameters associated with a command, wherein
    - the command is associated with the activation of the work item object, and
    - the identifying the command comprises the communication server accessing a user-interface-object command parameter table;
  - identifying a channel driver, wherein
    - the channel driver ~~comprises~~ is configured to execute the command, and
    - the identifying the channel driver comprises the communication server accessing a command table; and
  - causing the channel driver to issue the command from the communication ~~center server~~ to an outgoing communication channel of the communication channels.

2. (Original) The method of claim 1 wherein the incoming communication channel and the outgoing communication channel are the same.
3. (Original) The method of claim 1 further comprising: performing the command, wherein the command is performed by the outgoing communication channel.
4. (Original) The method of claim 1 wherein the providing the notification includes providing the notification in real time with the obtaining the event.
5. (Previously Presented) The method of claim 1 wherein the providing the notification includes invoking a notification module of the user interface.
6. (Original) The method of claim 1 wherein the activation of the work item object is associated with an accept work item command.
7. (Original) The method of claim 1 wherein the activation of the work item object is associated with a release work item command.
8. (Previously Presented) The method of claim 1 further comprising: sending the command to the channel driver.
9. (Previously Presented) The method of claim 8 wherein the sending the command to the channel driver comprises obtaining the command from the user interface by a communication server, wherein the communication server sends the command to the channel driver.

10. (Previously Presented) The method of claim 1 wherein the sending the command comprises sending the command to the channel driver for the incoming communication channel if the incoming communication channel and the outgoing communication channel are the same.

11-12. Cancelled

13. (Currently Amended) A method ~~for communicating~~ comprising:  
 obtaining an event communicated to a communication ~~center server~~ via an incoming communication channel of a plurality of communication channels, wherein the communication server is communicatively coupled to the plurality of communication channels via a plurality of channel drivers,  
 each communication channel of the communication channels has a media type,  
 and  
 at least two of the communication channels have different media types;  
 providing a notification of the event via the user interface, wherein the user interface comprises a web browser;  
 receiving an activation of a command object of the user interface, wherein the activation of the command object is received from one communication channel of the plurality of communication channels, and the command object is activated by an agent;  
 identifying one or more parameters associated with a command associated with the activation of the command object, wherein the identifying the command comprises the communication server accessing a user-interface-object command parameter table;  
 identifying a channel driver ~~comprising the command~~, wherein the channel driver is configured to execute the command, and  
 the identifying the channel driver comprises the communication server accessing a command table; and  
 causing the channel driver to issue the command from the communication ~~center server~~ to an outgoing communication channel of the communication channels.

14-16. Cancelled

17. **(Currently Amended)** A computer program product ~~for presenting a user interface for communicating~~ comprising:
- an obtaining module to obtain an event communicated to a communication ~~center~~ server via an incoming communication channel of a plurality of communication channels, wherein  
**the communication server is communicatively coupled to the plurality of communication channels via a plurality of channel drivers,**
    - each communication channel of the communication channels has a media type, at least two of the communication channels have different media types, and the event corresponds to a work item;
  - a notification module to provide a notification of the work item via a user interface,  
**wherein**  
**the user interface comprises a web browser;**
    - a work item object, wherein
      - the work item object is associated with the work item;
    - a receiving module to receive an activation of the work item object, wherein
      - the activation of the work item object is further associated with selecting one communication channel of the plurality of communication channels
      - the work item object is activated by an agent,
      - the activation of the work item object causes a channel driver **comprising**  
**configured to execute** the command to be identified; and
      - the channel driver issues the command from the communication ~~center~~ server to an outgoing communication channel of the plurality of communication channels;
  - a first identifying module to identify **one or more parameters associated with** the command, wherein  
**the communication server comprises the first identifying module,**
    - the command is associated with the activation of the work item object, and
    - the first identifying module comprises a first accessing module for accessing a

**user interface object command parameter** table;

a second identifying module to identify the channel driver associated with the command, wherein

**the communication server comprises the second identifying module, and**

the second identifying module comprises a second accessing module for accessing a command table; and

a physical computer readable medium, configured to store the computer program product.

18. (Previously Presented) The computer program product of claim 17, wherein the incoming communication channel and the outgoing communication channel are the same.

19. (Currently Amended) A computer program product ~~for communicating~~ comprising:

a notification object to provide a notification of an event communicated to a communication ~~center server~~ via an incoming communication channel of a plurality of communication channels, wherein

**the communication server is communicatively coupled to the plurality of communication channels via a plurality of channel drivers,**

each communication channel of the communication channels has a media type, and

at least two of the communication channels have different media types;

a command object, wherein

activation of the command object is associated with a command,

the activation of the command object is received from one communication channel of the plurality of communication channels,

the activation of the command object causes a channel driver ~~comprising~~ **configured to execute** the command to be identified,

the command object is activated by an agent, and

the channel driver issues the command from the communication ~~center server~~ to an outgoing communication channel of the communication channels;

a first identifying module to identify the one or more parameters associated with command, wherein  
the communication server comprises the first identifying module,  
the command is associated with the activation of the work item object, and  
the first identifying module comprises a first accessing module for accessing a  
user-interface-object command parameter table;  
a second identifying module to identify the channel driver associated with the command,  
wherein  
the communication server comprises the second identifying module, and  
the second identifying module comprises a second accessing module for accessing  
a command table; and  
a physical computer readable medium, configured to store the computer program product.

20. (Previously Presented) The computer program product of claim 19  
wherein  
the incoming communication channel and the outgoing communication channel are the  
same.

21. (Currently Amended) A computer system comprising:  
a processor;  
a display, coupled to said the processor;  
computer readable medium coupled to said the processor; and  
computer code, encoded in said the computer readable medium,  
configured to cause said the processor to communicate using at least one  
communication channel of a plurality of communication channels,  
wherein  
the processor is communicatively coupled to the plurality of  
communication channels via a plurality of channel drivers,  
each communication channel of the communication channels has a media  
type, and  
at least two of the communication channels have different media types,

by virtue of being configured to cause ~~said the~~ processor to:

obtain an event communicated via an incoming communication channel of the communication channels, wherein

the event corresponds to a work item available via the incoming communication channel;

provide a notification of the work item via a user interface presented on the display wherein

**the user interface comprises a web browser;**

receive an activation of a work item object of the user interface, wherein the work item object is associated with the work item,

the activation of the work item object is associated with selecting one communication channel of the plurality of communication channels,

the work item object is activated by an agent,

the activation of the work item object causes a channel driver

**comprising configured to execute** a command associated with the activation of the work item object to be identified, and

the channel driver issues the command associated with the activation of the work item object to an outgoing communication channel of the communication channels;

identify **one or more parameters associated with** the command

associated with the activation of the work item object; wherein

the computer code configured to cause the processor to identify the command comprises computer code to cause the processor to access a **user-interface-object command parameter** table, and

identify the channel driver associated with the command, wherein

the computer code configured to cause the processor to identify the channel driver comprises computer code to cause the processor to access a command table.

22. (Currently Amended) A computer program product comprising:  
 a database comprising:  
 a communication channel table comprising information regarding a  
 communication channel;  
 a user-interface-object command table comprising information regarding a user  
 interface object of a user interface wherein  
the user interface is used to communicate via the communication  
 channel,  
the user interface comprises a web browser, wherein  
 the information regarding the user interface object comprises a command  
 associated with activation of the user interface object, wherein  
and  
 the activation of the user interface object is received from one  
 communication channel of the plurality of communication  
 channels;  
 a channel driver table comprising information regarding a channel driver that  
 controls the operation of the communication channel and is operable to  
 provide an event from the communication channel and to issue the  
 command to the communication channel;  
 an event table comprising information regarding the event; and  
 a command parameter table comprising information regarding one or more  
parameters associated with the command;  
 and  
 instructions to access the communication channel table, the user-interface-object  
command table, the channel driver table, the event table, and the command table  
 to communicate via the communication channel; and  
 a physical computer readable medium, configured to store the computer program product.

23. (Previously Presented) The computer program product of claim 22,  
 wherein  
 the communication channel table provides access to:



a channel ID of the communication channel;  
a media type of the communication channel; and  
a configuration ID of a configuration to which the communication channel belongs.

24. (Previously Presented) The computer program product of claim 22, wherein  
the event table provides access to  
an event ID of the event;  
an event name of the event; and  
a channel driver ID of the channel driver.

25. (Previously Presented) The computer program product of claim 22, wherein  
the command table provides access to:  
a command ID of the command;  
a command name of the command; and  
a channel driver ID of the channel driver.

26. (Previously Presented) The computer program product of claim 22, wherein said channel driver table comprises:  
a channel driver ID of the channel driver;  
a media type of the communication channel;  
a file name of the channel driver; and  
a media string that allows a media service associated with the channel driver to be invoked.

27. Cancelled.

28. (Previously Presented) The method of claim 1 wherein  
the activation of the work item object is associated with selecting from a list of a plurality  
of work items.

29. (Previously Presented) The method of claim 1 wherein the activation of the work item object is associated with one of a suspend work item command and a retrieve work item command.
30. (Previously Presented) The method of claim 1 wherein the activation of the work item object is associated with an initiate work item command.
31. (Previously Presented) The method of claim 1 wherein the activation of the work item object is associated with one of a blind transfer of work item command, a consultative transfer of work item command, and a conference command.
32. (Previously Presented) The method of claim 1 wherein the user interface comprises a plurality of user interfaces, wherein each user interface of the user interfaces is associated with an agent of a plurality of agents;  
and further comprising:  
determining one agent of the agents to be notified of the event, wherein the providing the notification comprises providing the notification to the one agent via the user interface associated with the one agent.
33. (Previously Presented) The method of claim 1 further comprising:  
determining the command to be issued from a context of the work item object when the work item object is activated.
34. (Previously Presented) The computer program product of claim 17, further comprising:  
a causing module to cause the command to be issued to the outgoing communication channel.
35. (Previously Presented) The computer program product of claim 17, further comprising:

an assignment module to determine an assignment of an agent to the work item.

36. (Previously Presented) The computer program product of claim 22, wherein the channel driver table comprises information regarding a plurality of channel drivers.

37. (Previously Presented) The computer program product of claim 22, wherein the communication channel table comprises information regarding a plurality of communication channels.

38. (Canceled)

39. (Currently Amended) A computer program product ~~for presenting a user interface for communicating~~ comprising:

a user interface object, wherein

**the user interface object is displayed using a user interface comprising a web browser;**

a receiving module configured to receive an activation of the user interface object, wherein

each communication channel of a plurality of communication channels has a media type,

at least two communication channels of the communication channels have different media types,

the activation of the user interface object is received at a communication ~~center~~ **server**, from one communication channel of the plurality of communication channels,

**the communication server is communicatively coupled to the communication channels via a plurality of channel drivers.**

the user interface object is activated by an agent,

the activation of the user interface object is associated with a command,

the activation of the user interface object causes a channel driver associated with

the command to be identified;

an accessing module configured to access a ~~user interface object~~ command parameter table comprising ~~information regarding the user interface object, wherein~~ the information regarding the user interface object comprises one or more parameters associated with the command associated with the activation of the user interface object;

a channel driver module configured to cause the channel driver to issue the command from the communication ~~center~~ server to an outgoing communication channel of the communication channels; and

a physical computer readable medium storing the modules of the computer program product.

40. (Previously Presented) The computer program product of claim 39 further comprising:

an event handling module configured to handle an event from an incoming communication channel of the communication channels.

41. (Previously Presented) The computer program product of claim 40 further comprising:

a notifying module configured to provide a notification of the event.

42. (Previously Presented) The computer program product of claim 40 further comprising:

a responding module configured to perform an event response to the event.

43. (Previously Presented) The computer program product of claim 39 further comprising:

a status object;

a status updating module configured to update a status of an agent using the user interface to one of ready and not ready when the status object is activated.

44. (Previously Presented) The computer program product of claim 39 further

comprising:

a status changing module configured to change a status of an agent using the user interface to one of ready and not ready.

45. (Previously Presented) The computer program product of claim 39 further comprising:

an assigning module configured to assign an agent to receive a notification of an event;  
and

a notifying module configured to provide the notification to the agent.

46. (Currently Amended) A computer program product comprising:  
a database comprising:

a user interface object command table comprising information regarding a user interface object of a user interface used to communicate with a communication channel, wherein

**the user interface comprises a web browser,**

the information regarding the user interface object comprises a command associated with activation of the user interface object, **and**

the activation of the user interface object is received at a communication **center server,** from one communication channel of a plurality of communication channels, **and**

**the communication server is communicatively coupled to the communication channels via a plurality of channel drivers;**

instructions to access the user interface object command table when the user interface is to display information related to a communication via the communication channel;

instructions to cause a channel driver to issue the command from the communication **center server** to an outgoing communication channel of the communication channels; and

a physical computer readable medium, configured to store the computer program product.

47. (Previously Presented) The computer program product of claim 46

wherein the database further comprises:

a communication channel table comprising information regarding the communication channel.

48. (Previously Presented) The computer program product of claim 47, wherein the communication channel table comprises information about a plurality of communication channels.

49. (Previously Presented) The computer program product of claim 48 wherein the database further comprises:  
a channel driver table comprising information about a plurality of channel drivers,  
wherein each channel driver of the channel drivers controls the operation of one communication channel of the communication channels.

50. (Previously Presented) The computer program product of claim 46 wherein the database further comprises:  
a channel driver table comprising information about a channel driver that controls the operation of the communication channel.

51. (Previously Presented) The computer program product of claim 46 wherein the database further comprises:  
a command table comprising information regarding a command sent to the communication channel.

52. (Previously Presented) The computer program product of claim 46 wherein the database further comprises:  
an event table comprising information regarding an event originating in response to a communication received from the communication channel.

53. (Previously Presented) The computer program product of claim 52 wherein the database further comprises:  
an event response table comprising information regarding an event response to be

performed in response to the event.

54. **(Currently Amended)** A computer program product comprising:  
a database comprising:

~~an object~~ a command table, wherein the ~~object~~ command table comprises information regarding a user interface object of a user interface used to communicate via a communication channel, wherein the user interface comprises a web browser, the information regarding the user interface object comprises a command associated with activation of the user interface object, **and** the activation of the user interface object is received at a communication ~~center~~ server, from one communication channel of the plurality of communication channels, and the communication server is communicatively coupled to the communication channels via a plurality of channel drivers; and a communication channel table, wherein the communication channel table comprises information regarding the communication channel associated with the user interface object; **and** first instructions configured to access the ~~object~~ command table and the communication channel table to communicate via the communication channel; second instructions configured to cause a channel driver to issue the command from the communication ~~center~~ server to an outgoing communication channel of the communication channels; and a physical computer readable medium, configured to store the computer program product.

55. **(Currently Amended)** The computer program product of claim 54 wherein the ~~object~~ command table further comprises information regarding an action to be performed when the user interface object is activated.

56. **(Previously Presented)** The computer program product of claim 55 wherein

the action comprises issuing a command to the communication channel.

57. (Previously Presented) The computer program product of claim 55 wherein the action comprises setting an agent status to one of ready and not ready.

58. (Currently Amended) The computer program product of claim 54 wherein the ~~object table~~ user interface object further comprises a notification object.

59. (Currently Amended) A computer program product ~~for communicating~~ comprising:  
 a user interface comprising at least one user interface object configured to be activated by an agent, wherein  
 activation of one of the at least one user interface object is associated with issuing a command to one communication channel of a plurality of communication channels,  
 the activation of the user interface object is received at a communication ~~center server~~, from the one communication channel of the plurality of communication channels, wherein  
the communication server is communicatively coupled to the communication channels via a plurality of channel drivers,  
 each communication channel of the communication channels has a media type,  
 at least two communication channels of the communication channels have different media types, and  
 the activation causes the communication server to identify a channel driver ~~comprising~~ configured to execute the command ~~to be identified~~;  
 an accessing module configured to access a ~~user interface object command~~ table comprising information regarding the at least one user interface object, wherein the information regarding the at least one user interface object comprises a respective command associated with activation of each user interface object;



a channel driver module configured to cause the channel driver to issue the command from the communication **center server** to an outgoing communication channel of the communication channels; and  
a physical computer readable medium storing the computer program product.

60. (Previously Presented) The computer program product of claim 59 wherein the user interface is configured to communicate with a communication server, and the communication server causes the command to be issued to the one communication channel.

61. (Previously Presented) The computer program product of claim 60 wherein the communication server further receives an indication of activation of the user interface object.

62. (Previously Presented) The computer program product of claim 59 wherein the channel driver is communicatively coupled to the one communication channel to issue the command.

63. (Previously Presented) The computer program product of claim 59 wherein the channel driver is one of a plurality of channel drivers, wherein each channel driver of the channel drivers is associated with an associated communication channel of the plurality of communication channels.

64. (**Currently Amended**) The computer program product of claim 59 further comprising:  
a database comprising:  
a command **parameter** table comprising information regarding the command;  
and

a ~~user interface object~~ command table comprising information regarding the user interface object and the command to be issued upon activation of the user interface object.

65. (Previously Presented) The computer program product of claim 64 wherein the database further comprises:

a configuration table comprising information regarding a configuration for a user of the user interface, wherein the configuration determines whether the command is available to the user.

66. (Currently Amended) The computer program product of claim 64 wherein the command parameter table and the ~~user interface object~~ command table are accessed to cause the channel driver to issue the command.

67. (Currently Amended) An apparatus for communicating comprising: obtaining means for obtaining an event communicated to a communication ~~center~~ server via an incoming communication channel of a plurality of communication channels, wherein the communication server is communicatively coupled to the communication channels via a plurality of channel drivers.

each communication channel of the communication channels has a media type, at least two communication channels of the communication channels have different media types, and

the event corresponds to a work item available via the incoming communication channel;

notifying means for providing a notification of the work item via a user interface,

wherein

the user interface comprises a web browser;

receiving means for receiving an activation of a work item object of the user interface,

the work item object being associated with the work item, wherein the activation of the work item object is associated with selecting one communication channel of the plurality of communication channels, the work item object is activated by an agent, the activation of the work item object causes a channel driver **comprising configured to execute** a command associated with the activation of the work item object to be identified, and the channel driver issues the command associated with the activation of the work item object from the communication **center server** to an outgoing communication channel of the communication channels; and accessing means for accessing a **user interface object command** table comprising information regarding the work item object, wherein the information regarding the work item object comprises the command associated with the activation of the work item object.

68. (Previously Presented) The apparatus of claim 67 wherein the incoming communication channel and the outgoing communication channel are the same.

69. (Previously Presented) The apparatus of claim 67 wherein the command is performed by the outgoing communication channel.

70. (Previously Presented) The apparatus of claim 67 wherein the notifying means comprise real-time notifying means for providing the notification in real time with the obtaining the event.

71. (Previously Presented) The apparatus of claim 67 wherein the notifying means comprises invoking means for invoking a notification module of the user interface.

72. (Previously Presented) The apparatus of claim 67 wherein the activation of the work item object is associated with an accept work item command.

73. (Previously Presented) The apparatus of claim 67 wherein the activation of the work item object is associated with a release work item command.

74. (Previously Presented) The apparatus of claim 67 further comprising:  
sending means for sending the command to the channel driver.

75. (Previously Presented) The apparatus of claim 74 wherein the sending means comprise command obtaining means for obtaining the command from the user interface by a communication server, wherein the communication server sends the command to the channel driver.

76. (Previously Presented) The apparatus of claim 67 wherein the sending means send the command to the channel driver for the incoming communication channel if the incoming communication channel and the outgoing communication channel are the same.

77. (Cancelled)

78. (Previously Presented) The apparatus of claim 67 wherein the activation of the work item object is associated with selecting from a list of a plurality of work items.

79. (Previously Presented) The apparatus of claim 67 wherein the activation of the work item object is associated with one of a suspend work item command and a retrieve work item command.

80. (Previously Presented) The apparatus of claim 67 wherein the activation of the work item object is associated with an initiate work item command.

81. (Previously Presented) The apparatus of claim 67 wherein the activation of the work item object is associated with one of a blind transfer of work item command, a consultative transfer of work item command, and a conference command.

82. (Previously Presented) The apparatus of claim 67 wherein the user interface comprises a plurality of user interfaces, wherein each user interface of the user interfaces is associated with an agent of a plurality of agents;  
and further comprising:  
agent determining means for determining one agent of the agents to be notified of the event, wherein the providing the notification comprises providing the notification to the one agent via the user interface associated with the one agent.

83. (Previously Presented) The apparatus of claim 67 wherein the issuing means comprise command determining means for determining the command to be issued from a context of the work item object when the work item object is activated.

84. **(Currently Amended)** An apparatus comprising:  
obtaining means for obtaining an event communicated to a communication ~~center~~ **server** via an incoming communication channel of a plurality of communication channels, wherein  
**the communication server is communicatively coupled to the communication channels via a plurality of channel drivers.**  
each communication channel of the communication channels has a media type,  
and  
at least two of the communication channels have different media types;  
notifying means for providing a notification of the event via the user interface, **wherein the user interface comprises a web browser;**  
receiving means for receiving an activation of a command object of the user interface, the command object being associated with a command related to the event, wherein

the activation of the command object is received from one communication channel of the plurality of communication channels,  
 the command object is activated by an agent,  
 the receiving the activation causes a channel driver comprising the command to be identified, and  
 the channel driver issues the command from the communication **center server** to an outgoing communication channel of the communication channels; and  
 accessing means for accessing a **user interface object command** table comprising information regarding the command object, wherein  
 the information regarding the command object comprises the command associated with the activation of the command object.

85. **(Currently Amended)** A computer program product comprising:  
 obtaining instructions to obtain an event communicated to a communication **center server** via an incoming communication channel of a plurality of communication channels, wherein  
**the communication server is communicatively coupled to the communication channels via a plurality of channel drivers.**  
 each communication channel of the communication channels has a media type,  
 at least two communication channels of the communication channels have different media types, and  
 the event corresponds to a work item available via the incoming communication channel;  
 notifying instructions to provide a notification of the work item via a user interface,  
**wherein**  
**the user interface comprises a web browser;**  
 receiving instructions to receive an activation of a work item object of the user interface,  
 the work item object being associated with the work item, wherein  
 the activation of the work item object is associated with selecting one communication channel of the plurality of communication channels,  
 the work item object is activated by an agent,

the activation of the work item object causes a channel driver **comprising**  
**configured to execute** a command associated with the activation to be  
 identified, and

the channel driver issues the command associated with the activation of the work  
 item object from the communication **center server** to an outgoing  
 communication channel of the communication channels; and

accessing instructions to access a **user interface object command** table comprising  
 information regarding the work item object, wherein  
 the information regarding the work item object comprises the command  
 associated with the activation of the work item object; and

a computer-readable storage medium, configured to store the computer program product.

86. (Previously Presented) The computer program product of claim 85  
 wherein  
 the obtaining instructions are capable of obtaining the event when the incoming  
 communication channel and the outgoing communication channel are the same.

87. (Previously Presented) The computer program product of claim 85  
 wherein the command is performed by the outgoing communication channel.

88. (Previously Presented) The computer program product of claim 85  
 wherein  
 the notifying instructions comprise real-time notifying instructions to provide the  
 notification in real time with the obtaining the event.

89. (Previously Presented) The computer program product of claim 85  
 wherein  
 the notifying instructions comprise invoking instructions to invoke a notification module  
 of the user interface.

90. (Previously Presented) The computer program product of claim 85  
 wherein

the activation of the work item object is associated with an accept work item command.

91. (Previously Presented) The computer program product of claim 85 wherein the activation of the work item object is associated with a release work item command.

92. (Previously Presented) The computer program product of claim 85 further comprising:  
sending instructions for sending the command to the channel driver.

93. (Previously Presented) The computer program product of claim 85 the sending instructions further comprise command obtaining instructions for the command from the user interface by a communication server, wherein the communication server sends the command to the channel driver.

94. (Previously Presented) The computer program product of claim 85 further comprising:  
sending instructions for sending the command to the channel driver for the incoming communication channel if the incoming communication channel and the outgoing communication channel are the same.

95. (Previously Presented) The method of claim 13 wherein the activation of the command object is associated with selecting one communication channel of the plurality of communication channels.

96. (Previously Presented) The method of claim 13 wherein the activation of the command object is associated with selecting from a list of a plurality of work items.

97. (Previously Presented) The method of claim 13 wherein the activation of the command object is associated with one of a suspend work item command and a retrieve work item command.



98. (Previously Presented) The method of claim 13 wherein the activation of the command object is associated with an initiate work item command.

99. (Previously Presented) The method of claim 13 wherein the activation of the command object is associated with one of a blind transfer of work item command, a consultative transfer of work item command, and a conference command.

100. (Previously Presented) The method of claim 13 wherein the user interface comprises a plurality of user interfaces, wherein each user interface of the user interfaces is associated with an agent of a plurality of agents;  
and further comprising:  
determining one agent of the agents to be notified of the event, wherein the providing the notification comprises providing the notification to the one agent via the user interface associated with the one agent.

101. (Previously Presented) The method of claim 13 further comprising:  
determining the command to be issued from a context of the command object when the command object is activated.